

Best choice, Brightest price

KOLIDA
KOLIDA INSTRUMENT

PD-5 SERIES

HAND-HELD DISTANCE METER



SPECIFICATIONS

	PD-58	PD-56	PD-54
Measuring Range (use target plate for longer range)	0.05 m~80 m	0.05 m~60 m	0.05 m~40 m
Measuring Accuracy	±1.5mm Typical*		
Minimum Reading	1mm		
Laser Class	II		
Laser Type	635 nm, < 1 mW		
Auto Power-off	180 second		
Illumination	✓		
Continuous Measurement	✓		
Plane Area Measurement, Volume Measurement	✓		
Triangle Measurement	✓		-
Ladder type Measurement	✓		-
Pythagoras Measurement	✓		
Addition/Subtraction	✓		
Historical Storage	30	20	-
Obliquity measurement Range*	±45°		-
Obliquity measurement Accuracy*	±0.3°		-
Battery Life	(Type AAA, 4×1.5V) Up to 5000 Measurements	(Type AAA, 2×1.5V) Up to 5000 Measurements	
Dimension & Weight	130×55×30 mm, 150 g	118×50×30 mm, 120 g	
Temperature Range	-25℃ ~ +70℃(Storage) -10℃ ~ +50℃(Operation)		



APPLICATIONS



KOLIDA
KOLIDA INSTRUMENT

GUANGDONG KOLIDA INSTRUMENT CO.,LTD.

Add: 2/F, Surveying & Mapping Building (He Tian Building),NO.24-26, Tianhe Software Park,
Ke Yun Road, Guangzhou 510665, China

Tel: +86-20-85542075 Fax: +86-20-85542136

Email:export@kolidainstrument.com www.kolidainstrument.com